

Fiber Optic SFP DFB 1310nm 2.67G Transceiver with APD Photodiode and DDMI

Data Sheet

OFD3546



The OFD3546 transceiver module operates at a wavelength of 1310 nm and at 2.67 Gb/s for OC-3, OC-12 and OC-48 long reach applications.

Features

- Hot-pluggable
- Single +3.3 V supply
- Duplex LC connector interface
- Distributed Feedback 1310 type LD
- Low power dissipation
- OC-48/STM-16 Long Reach
- APD receiver
- Power Output: -2 to +3 dBm
- 50 km link distance
- Multi data rates from 100Mbps to 2.7Gbps
- Internal Digital Diagnostics calibration
- Digital Diagnostics Monitoring for SFF-8472 compatible
- Multi-Source Agreement (MSA) for Small Form Factor Pluggable (SFP) Compliant

Applications

- Telecommunications and Data Communications system networks
- SONET OC-12, OC-48 LR-1/STM-16 L16.1
- SONET OC-3
- Gigabit Ethernet
- Point-to-Point networking
- Metro Access Rings
- 1x/ 2x Fiber Channel
- 100Base Fast Ethernet

Description

The OFD3546 transceiver provides signal conversion and processing for serial optical data communication applications. It operates over single mode fiber by converting 1310 nm wavelength lightwave information into an electrical signal and vice versa at a data rate of 2.67 Gb/s.

Housed in a compact metal package, the transceiver module consists of a transmitter and receiver optical subassembly coupled with a duplex LC receptacle. A high-speed uncooled DFB laser diode operates as light source while an APD photodiode subsequently acts as a detector.

This dual-fiber connector transceiver is designed for use in telecom and datacom network systems at 2.67 Gb/s for SONET OC-3, OC-12, OC-48 LR-1/SDH STM-16 L16.1, Fast Ethernet, Gigabit Ethernet and 1x/2x Fiber Channel applications.

Transceiver Monitoring Interface

OFD3546 provides an enhanced monitoring interface, which allows real-time access to device operating parameters such as transceiver temperature, laser bias current, transmitted optical power, received optical power and transceiver supply voltage. It also defines a sophisticated system of alarm and warning flags, which alerts end-users when particular operating parameters are outside of a normal factory-set range. The monitoring interface makes use of two wire address 1010001X (A2h) and is backward compatible with the Small Form Pluggable Multi-Source Agreement (SFP MSA).

Serial Identification (EEPROM)

An SFP having module definition 4 provides access to sophisticated identification information that describes the SFP transceiver’s capabilities, standard interface, manufacturer and other information. An EEPROM containing the detailed product information and digital diagnostic function for the host equipment is accessed by the 2-wire serial CMOS EEPROM protocol. See SFP MSA for detailed description.

Performance Specifications

Absolute Maximum Ratings

Stresses in excess of the absolute maximum ratings can cause damage to the optical device. Operations of the optical device are suggested to remain within the recommended operating conditions. Exposure to the absolute maximum ratings for extended periods can adversely affect device reliability.

| Parameter | Symbol | Minimum | Maximum | Unit |
|---------------------|-----------------|---------|---------|------|
| Storage Temperature | T _S | -40 | +85 | °C |
| Supply Voltage | V _{CC} | 0 | 4.0 | V |
| Relative Humidity | RH | 5 | 85 | % |

Recommended Operating Conditions

| Parameter | Symbol | Minimum | Typical | Maximum | Unit |
|-----------------------|-----------------------------------|---------|---------|---------|------|
| Operating Temperature | T _{OP} | 0 | | 70 | °C |
| Supply Voltage | V _{CC} | 3.1 | 3.3 | 3.5 | V |
| Supply Current | I _{TX} + I _{RX} | | 200 | 300 | mA |

Safety

Laser Compliance Statement

The OFD3546 is classified as a Class I Laser Product and complies with IEC 60825-1 and FDA 21 CFR 1040.10 and 1040.11. The transceiver must be operated under recommended operating conditions. Because the transceiver is designed to be inherently eye safe, it does not require open fiber control thus eliminating complex electronics or mechanics.

Caution - use of device other than those specified herein may result in hazardous laser radiation exposure or other damage. Please embrace all customary precautions and discretion while handling this device.

Transmitter Electro-Optical Interface (T_C = 0~70°C; V_{CC}T,R = 3.1V < V_{CC} < 3.5V)

| Parameter | Symbol | Minimum | Maximum | Unit |
|--|---------------------------------|-----------------|-----------------------|-------|
| Transmitter Differential Input Voltage | TD +/- | 400 | 2000 | mVp-p |
| Optical Output Power ¹ | P _O | -2 | +3 | dBm |
| Optical Extinction Ratio ¹ | E _R | 8.2 | | dB |
| Center Wavelength ¹ | λ _C | 1280 | 1340 | nm |
| Spectral Width ¹ | Δλ | | < 1 | nm |
| Side Mode Suppression Ratio ¹ | SMSR | 30 | | dB |
| Optical Rise/ Fall Time ² | t _r / t _f | | 0.15 | nsec |
| Tx_Fault - HIGH | V _{Fault_H} | 2 | V _{CC} | V |
| Tx_Fault - LOW | V _{Fault_L} | V _{ee} | V _{ee} + 0.5 | V |
| Tx_Disable - High | V _{Disable_H} | 2 | V _{CC} | V |
| Tx_Disable - LOW | V _{Disable_L} | V _{ee} | V _{ee} + 0.8 | V |

Note:

1. Measured at 2488.32 Mbps, PRBS 2²³-1, NRZ.
2. 20%-80%

Receiver Electro-Optical Specifications (T_C = 0~70°C; V_{CC}T,R = 3.1V < V_{CC} < 3.5V)

| Parameter | Symbol | Minimum | Typical | Maximum | Unit |
|---|-----------------------|---------|---------|---------|-------|
| Receiver Differential Output Voltage | RD +/- | 600 | 800 | | mVp-p |
| Receiver Overload ^{1,2} | P _{IN} MAX | -8 | | | dBm |
| Receiver Sensitivity ^{1,2} | P _{IN} MAX | | | -28 | dBm |
| Operating Center Wavelength | λ _C | 1270 | | 1620 | nm |
| Receiver LOS Assert Level ² | P _{RX_LOS A} | -45 | | | dBm |
| Receiver LOS Deassert Level ² | P _{RX_LOS D} | | | -28.5 | dBm |
| Receiver Loss of Signal Hysteresis ² | | 0.5 | 2 | | dB |

Note:

1. With BER better than or equal to 1x10⁻¹².
2. Measured in center of eye opening with 2²³-1 PRBS, NRZ.

Pin Assignment




Figure 1. SFP Transceiver Electric Pad Layout

OFD3546 SFP TRANSCEIVER DATA SHEET




Figure 2. Diagram of Host Board Connector Block Pin

Pin Description and Plug-in Sequence¹ (1-Grd, 2-Power, 3-Signal)

| Pin No. | Name | Description | Plug-in Sequence | Notes |
|---------|-------------|------------------------------|------------------|--|
| 1 | VeeT | Transmitter Ground | 1 | Circuit ground is internally isolated from chassis ground. |
| 2 | TX Fault | Transmitter Fault Indication | 3 | Open-Collector outputs, asserted when LD and/or APC function fail. |
| 3 | TX Disable | Transmitter Disable | 3 | Disable when high voltage (>2.0V or Open). |
| 4 | MOD-DEF 2 | Module Definition 2 | 3 | Should be pulled up with 4.7k - 10 kΩ on host board to voltage between 2.0V and 5.5V. MOD-DEF (0) pulls line low to indicate module is plugged in. |
| 5 | MOD-DEF 1 | Module Definition 1 | 3 | See notes for Pin 4. |
| 6 | MOD-DEF 0 | Module Definition 0 | 3 | See notes for Pin 4. |
| 7 | Rate Select | Bandwidth Selection | 3 | No connection required. |
| 8 | LOS | Loss of Signal | 3 | LOS is Open-Collector output. Should be pulled up with 4.7k - 10kΩ on host board to a voltage between 2.0V and 5.5V. Logic 0 indicates normal operation; logic 1 indicates loss of signal. |
| 9 | VeeR | Receiver Ground | 1 | See notes for Pin 1. |
| 10 | VeeR | Receiver Ground | 1 | See notes for Pin 1. |
| 11 | VeeR | Receiver Ground | 1 | See notes for Pin 1. |
| 12 | RD- | Inv. Received Data Out | 3 | |
| 13 | RD+ | Received Data Out | 3 | |
| 14 | VeeR | Receiver Ground | 1 | See notes for Pin 1. |
| 15 | VccR | Receiver Power | 2 | |
| 16 | VccT | Transmitter Power | 2 | |

OFD3546 SFP TRANSCEIVER DATA SHEET

| | | | | |
|----|------|-----------------------|---|----------------------|
| 17 | VeeT | Transmitter Ground | 1 | See notes for Pin 1. |
| 18 | TD+ | Transmit Data In | 3 | |
| 19 | TD- | Inv. Transmit Data In | 3 | |
| 20 | VeeT | Transmitter Ground | 1 | See notes for Pin 1. |


Note:

1. Pin engagement sequence during hot plugging.


Physical Characteristics

Outline Diagram

Dimensions for the device package are given in millimeters.



Recommended Interface Diagram



Additional Information

Contact

For additional information, product specifications, or information about Optocom:

Internet: <http://www.optocom.com>

Email: sales@optocom.com

Tel: +1 978 988 8711

Fax: +1 978 988 8722

©2005 Optocom Corporation. All rights reserved. Information in this document is believed to be accurate and reliable and is subject to change without notice. Optocom Corporation will not be held liable for technical or editorial errors or omissions contained herein. Reproduction in whole or in part is prohibited without prior written consent of the copyright owner and no responsibility will be assumed by Optocom Corporation for any infringements of third parties. All other brand or product names mentioned are the trademarks or registered trademarks owned by their respective companies or organizations.